

# Pro Felt & Tissue Adhesive

## Product properties

Ready-mixed, transparent, reinforced adhesive.

## Labelling



## Product use

Used for hanging wall coverings such as glass felt, pre-treated glass felt and lightweight glass and non-woven wallpapers in dry rooms.

## Substrate

The substrate must be clean, dry, firm and sustainable.

## Treatment

Clean previously painted surfaces with Basic Cleaner.

Fill any cracks and holes with filler.

Prime with Primer if the substrate is chalking or very absorbent.

Sand glossy surfaces matt.

## Application

Apply on wall using brush, roller or spray gun.

Allow the adhesive to dry briefly before hanging the wall covering.

Condensation must be prevented during drying/curing.

## Good practice

Ensure good ventilation during and after hanging.

## Expected result

Uniform and well fastened to substrate.

Can be painted over when wall covering and adhesive are completely dry.

Exercise care in loading the substrate until the adhesive is fully cured.

## Environmental information

Minimize your paint waste by pre-estimating how much adhesive you need.  
Remove as much adhesive as possible from tools before cleaning.  
Adhesive and cleaning fluid must not be poured down drains, but collected and disposed of as environmental waste.  
Empty and dry packaging should be sorted as plastic, metal handles should be removed and sorted as metal.  
Store excess adhesive correctly so that leftovers can be used and environmental impact is minimised.

## Storage

Cool, frost free and tightly closed

## Protection equipment

Protect skin and eyes from splashes with suitable clothing, gloves and glasses.  
Avoid inhalation of spray mist and grinding dust.  
Wear suitable protective equipment, see safety data sheet for further information.

## Technical Data

Density (kgs/l)	1.04
Solids Weight %	20
Solids Vol. %	16
Nominal spreading rate (m²/ltr.)	4
Long spreading rate (m²/l.)	5
Min. working temp. during application and drying/curing	Min. +15°C
Humidity	Max. humidity 80 % RH.
Drying time at 20° C, 60 % RH (Hours)	3
Dilution	Do not dilute
Cleaning of Tools etc.	Water
Country of Origin	Denmark

## Current TDS Version

July 2025

## Replaces TDS Version

February 2025